**LISTING OF CLAIMS**

1.    (currently amended)    An    electronic    <u>user</u>    device,
comprising:

    <u>a receiving component for receiving messages intended</u>
<u>for said user;</u>

    a    plurality    of    interfaces    for    connecting    <u>message</u>
<u>rendering</u>  output  units  to  said  device,

    a    control    unit    for    controlling    the    routing    of
messages, said messages being determined to be presented to
a  user  of  said  device  via  at  least  one  of  said  <u>message</u>
<u>rendering</u>  output  units,  said  control  unit  being  configured
for:

       determining  at  least  one  of  said  <u>message  rendering</u>
       output  units  for  routing  a  message  to  based  on  a
       results  of  a  message  classification  process  wherein
       said    message    classification    process    comprises
       analysis  of  said  message  and  dynamic  classification
       of  said  message  based  on  at  least  one  of  message
       content    analysis,    presentability,    sender    and
       confidentiality  level,  and
       routing  said  message  to  an  interface  serving  said
       determined  <u>message  rendering</u>  output  unit.

2.    (currently  amended)    The  electronic  <u>user</u>  device  as
recited  in  claim  1,  further  comprising  a  stored  look-up
table  with  classification  levels  being  allocated  to  <u>message</u>
<u>rendering</u>  output  units.

3.    (currently  amended)    The  electronic  <u>user</u>  device  as
recited  in  claim  1,  further  comprising  a  classification

unit for running said classification process for classifying messages to be output.

4-7 (canceled)

8. (currently amended) The electronic user device as recited in claim 1, comprising an identification unit for identifying available connected message rendering output units and for making said control unit determine only one or more of said identified available message rendering output units for message routing.

9. (currently amended) The electronic user device as recited in claim 1, wherein said electronic device is a portable device.

10. (currently amended) A method for routing an electronic message from an electronic user device to a message rendering an output unit, comprising automatically controlled steps of:

    determining at least one of several message rendering output units based on a result of a message classification process, wherein said message classification process comprises analysis of said message and dynamic classification of said message based on at least one of message content analysis, presentability, sender and confidentiality level, and initiating said message to be routed to said determined message rendering output unit for presenting said message to said user of said electronic user device.

11. (original) The method as recited in claim 10, wherein said message is classified and said classification result is provided.

12-15. (canceled)

16. (currently amended) The method as recited in claim 10, wherein the availability of message rendering output units is checked, and wherein only one or more of the available message rendering output units can be determined for message routing.

17. (currently amended) A program storage device readable by a digital processing apparatus at an electronic user device and having a program of instructions which are tangibly embodied on the storage device and which are executable by the processing apparatus to perform a method of routing an electronic message received by said electronic user device from the an electronic user device to at least one of a plurality of message rendering output units, said method comprising:

    determining at least one of said message rendering output units based upon a message classification process, wherein said message classification process comprises analysis of said message and dynamic classification of said message based on at least one of message content analysis, presentability, sender and confidentiality level, and

    initiating said message to be routed to said determined message rendering output unit for presenting said message to a user of said electronic device.